

Ultracoat Oil Care

Natural oil resin in water dispersion for finishing treatments and maintenance work on wooden floors treated with products from the Ultracoat Oil range



WHERE TO USE

Final finishing treatments and routine maintenance of wooden floors treated with all the products from the **Ultracoat Oil** range.

Repairing small scratches made during laying operations on new wooden floors.

TECHNICAL CHARACTERISTICS

Ultracoat Oil Care is a solvent-free, natural drying oil in water dispersion for final finishing treatments and routine maintenance of wooden floors.

Ultracoat Oil Care used for routine maintenance operations helps maintain the original beauty of wooden floors as when they were originally laid.

Ultracoat Oil Care leaves the floor with a matt finish.

RECOMMENDATIONS

- Do not use **Ultracoat Oil Care** at temperatures lower than +10°C.
- Do not apply on external surfaces.
- Use only clean containers and tools.
- Environmental conditions and residual humidity in the wood when it is laid must conform to current norms and standards.
- Do not put leftover quantities of the product back into its original container.

- Do not use **Ultracoat Oil Care** for maintenance on wooden floors treated with oil which have a matt or grey appearance. In such cases, apply a coat of the product from the **Ultracoat Oil** range beforehand.

APPLICATION PROCEDURE

Finishing treatment

Follow the instructions on the Technical Data Sheet for the relative **Ultracoat Oil** product.

Routine maintenance

Small surfaces

Apply a coat of **Ultracoat Oil Care** with a cotton or microfiber cloth; make sure all the area to be treated is coated.

Large surfaces

Apply **Ultracoat Oil Care** with a single-head floor cleaner fitted with **Ultracoat Oil Pad**. If there are overlaps or if too much product is applied, remove using a single-head floor cleaner fitted with a green **Ultracoat Pad**.

Cleaning

Tools and residues of **Ultracoat Oil Care** may be cleaned with water while the product is still fresh.

CONSUMPTION

Absorbent floors: approx. 15 g/m².

PACKAGING

1 litre tanks.

Ultracoat Oil Care



TECHNICAL DATA (typical values)

PRODUCT IDENTITY

Consistency:	fluid
Colour:	whitish
Density (g/cm ³):	1.0

APPLICATION DATA (at +23°C - 50% R.H.)

Drying time:	30-60 minutes
Set to light foot traffic:	1 hour

STORAGE

24 months in its original, sealed packaging in a dry place.

SAFETY INSTRUCTIONS FOR PREPARATION AND INSTALLATION

Ultracoat Oil Care is not considered hazardous according to current norms and guidelines regarding the classification of mixtures. We recommend the use of protective gloves and goggles and take the usual precautions for handling chemical products.

Materials such as cleaning rags, paper wipes and protective clothing, which are contaminated with the product may spontaneously self-ignite some hours later. To avoid the risks of fires, all contaminated materials should be stored in metal containers with tight-fitting self-closing lids. Contaminated materials should be stored outside.

For further and complete information about the safe use of our product please refer to the latest version of our Material Safety Data Sheet.

PRODUCT FOR PROFESSIONAL USE.

WARNING

Although the technical details and recommendations contained in this product data sheet correspond to the best of our knowledge and experience, all the above information must, in every case, be taken as merely indicative and subject to confirmation after long-term practical application; for

this reason, anyone who intends to use the product must ensure beforehand that it is suitable for the envisaged application. In every case, the user alone is fully responsible for any consequences deriving from the use of the product.

Please refer to the current version of the Technical Data Sheet, available from our website www.mapei.com

LEGAL NOTICE

The contents of this Technical Data Sheet ("TDS") may be copied into another project-related document, but the resulting document shall not supplement or replace requirements per the TDS in force at the time of the MAPEI product installation.

The most up-to-date TDS can be downloaded from our website www.mapei.com.

ANY ALTERATION TO THE WORDING OR REQUIREMENTS CONTAINED OR DERIVED FROM THIS TDS EXCLUDES THE RESPONSIBILITY OF MAPEI.



Our Commitment To The Environment
MAPEI products assist Project Designers and Contractors create innovative LEED (The Leadership in Energy and Environmental Design) certified projects, in compliance with the U.S. Green Building Council.

All relevant references for the product are available upon request and from www.mapei.com



BUILDING THE FUTURE